

CI/SfB	(31)	Ln6
CAW P10		
Uniclass L6631:P91		

### Description

ME402 Compriband Ali-Tape PB is a high performance sealant tape which consists of a quality plasto-elastic butyl rubber adhesive / sealant applied to one side of an aluminised polyester film.

### Colour

Grey

### Packaging

ME402 Compriband Ali Tape PB is available with a thickness of 1.2 mm in 25 m length rolls in the following widths: 50, 75, 100 and 150 mm.

### Technical Information

Property	Test Method	Result
Thickness		1.2 mm
Density		1.5 g/cm <sup>3</sup>
Volatiles		0
Continuous Operating Temperature		-40°C to +80°C
Installation Temperature		+5°C to +40°C
Flammability Rating	DIN 4102	B2
Water Vapour Diffusion	DIN 53122	$\mu = 645,000$
Storage		Store in shaded dry conditions between +10°C and 25°C.
Shelf Life		12 months when stored as recommended in original unopened containers.

### Preparation

- Surfaces must be clean and free from dirt, loose material, grease and oils.
- It is recommended that rough or porous surfaces and overlaps are first treated with ME901 Butyl Primer or ME902 Butyl Spray Primer which will assist initial adhesion.

### Application

- Do not apply to very cold or frosted surfaces.
- Use of ME901 Butyl Primer may be considered under these circumstances.
- Trim the materials to the required length / shape allowing an overlap of at least 25 mm where the materials are to be joined.
- Ensure that there are no air pockets.
- Apply even pressure over the entire surface using non-abrasive tools e.g. cloth or preferably hand roller.
- Take care not to stretch or puncture the foil during application.

### Please Note

Do not use in permanently submerged joints. Check for compatibility with other sealants. Do not use in joints subject to traffic. The user is advised to conduct tests to determine the suitability of the product for the intended application.

### Health & Safety Precautions

Safety data sheet must be read and understood before use.



## ME402

### Compriband Ali-Tape PB

#### Usage / Purpose

ME402 Compriband Ali-Tape PB is intended for the internal and external sealing and repair of joints and overlaps in a wide variety of applications which includes amongst others shop fitting, facades, conservatories, air conditioning, and ventilation.

#### Key Benefits

- Tear resistant
- Weather and UV resistant
- Highly impermeable to water vapour and other gases
- Adheres without primer to many different substrates
- Simple, effective & easy to apply

**Technical Service**

tremco illbruck has a team of experienced Technical Service Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Service on 01942 251400.

**Guarantee / Warranty**

tremco illbruck products are manufactured to rigid standards of quality. Any product which has

been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.;No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.;tremco illbruck Ltd. reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



**tremco illbruck Limited**  
Coupland Road, Hindley Green  
WN2 4HT Wigan  
United Kingdom  
T: +44 1942 251400  
F: +44 1942 251410

info.uk@tremco-illbruck.com  
www.tremco-illbruck.co.uk